



**Clean Liquid Systems, LLC**  
21500 Kuykendahl Rd. Unit 200  
Spring, TX 77379  
Phone# 713-253-0100 / 713-253-5001  
dpalermo@cleanliquidsystems.com

## BULK FIBERGLASS ROLLS High Loft Media



Fiberglass Air Filter Media Available in a wide range of pad and roll sizes. Because all air filtration systems are different, one standard media cannot meet every requirement. With three media depths to choose from it is possible to find the right media for any fiberglass application.

### **Description:**

Although 1", 2" and 4" Fiberglass Air Filter Medias are designed for different applications, several qualities are common to all three styles:

### **Progressive Density:**

All fiberglass media consists of continuous filaments of high quality spun glass. These fibers are formed into a graded density blanket to provide maximum depth loading throughout the roll.

### **Product Performance Data**

Media Depth	Average Arrestance <sup>1</sup>	Capacity (grams)	Initial Resistance (in. w.g.)	Recommended Velocity (FPM)	MERV Rating <sup>2</sup>
1"	66%	127	0.35	350	3
2"	72%	154	0.65	350	3
4"	85%	260	0.18	500	4

<sup>1</sup> Based on ASHRAE Test Standard 52.1-1999

<sup>2</sup> Based on ASHRAE Test Standard 52.1-2007

### **Special Adhesive:**

Each individual fiber is coated with a specially designed adhesive gel. This adhesive enhances the media's dust holding ability by creating a "wicking" action not provided by competitive medias.

### **Color Coded Media:**

All Fiberglass Media is tinted on the downstream side for easy installation into frames or blanket systems. 1" and 2" Media– White, upstream; Blue, downstream  
4" Media– White, upstream; Yellow/Gold, downstream  
4" Commonly used on Compressor and engine intake and high dust load applications.